

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>DVX P SERIES</b>			
<b>DVX P8</b>	2-way passive speaker, 1x8" woofer with 2" VC, 1 x 1" Neodymium compression driver with 1.5" VC, rotatable plastic CD-Horn (90°x70°), 300W/RMS, 75Hz-20KHz, 125 dB SPL, Dimensions 250x425x260mm, weight 9.8kg/21.6lbs.	<b>5.184,00</b>	<b>6.480,00</b>
<b>DVX P10</b>	2-way passive speaker, 1x10" woofer with 2" VC, 1 x 1" Neodymium compression driver with 1.5" VC, rotatable plastic CD-Horn (90°x70°), 300W/RMS, 70Hz-20KHz, 127 dB SPL, Dimensions 290x510x310mm, weight 12.5kg/27.6lbs.	<b>5.756,00</b>	<b>7.195,00</b>
<b>DVX P12</b>	2-way passive speaker, 1x12" woofer with 3" VC, 1 x 1.4" Neodymium compression driver with 2.5" VC, rotatable plastic CD-Horn (90°x70°), 500W/RMS, 90Hz-20KHz, 133 dB SPL, Dimensions 370x625x395mm, weight 23.2kg/51.1lbs.	<b>8.228,00</b>	<b>10.285,00</b>
<b>DVX P15</b>	2-way passive speaker, 1x15" woofer with 3" VC, 1 x 1.4" Neodymium compression driver with 2.5" VC, rotatable plastic CD-Horn (90°x40°), 500W/RMS, 60Hz-20KHz, 133 dB SPL, Dimensions 430x690x450mm, weight 26.1kg/57.5lbs.	<b>8.956,00</b>	<b>11.195,00</b>
<b>DVX P215</b>	Passive speaker, 2x15" woofer with 3" VC, 1 x 1.4" Neodymium compression driver with 2.5" VC, rotatable plastic CD-Horn (90°x40°).	<b>14.388,00</b>	<b>17.985,00</b>
<b>DVX PSW15</b>	Passive subwoofer, 1x15" woofer with 3" VC, 1000W Peak power, 500W/RMS, 35Hz-200Hz, 132 dB SPL, Dimensions 470x627x600mm, weight 30.9kg/68.1lbs.	<b>6.580,00</b>	<b>8.225,00</b>
<b>DVX PSW18</b>	Passive subwoofer, 1x18" woofer with 4" VC, 2000W Peak power, 1000W/RMS, 28Hz-200Hz, 134 dB SPL, Dimensions 565x710x700mm, weight 44.1kg/97.2lbs.	<b>8.804,00</b>	<b>11.005,00</b>
<b>DVX PSW218</b>	Passive subwoofer, 2x18" woofer with 4" VC, 4000W Peak power, 2000W/RMS, 28Hz-200Hz, 140 dB SPL, Dimensions 565x1207x700mm, weight 74.2kg/163lbs.	<b>15.212,00</b>	<b>19.015,00</b>
<b>FIFTY LINE SERIES</b>			
<b>FIFTY 410T TOP</b>	Active Full range speaker 4x10" woofers, 2x1.4 drivers , 2x tilted horn, 1500 W RMS class D AMP , flyable with accessories, coverage H50° V+15° -35°	<b>23.468,00</b>	<b>29.335,00</b>
<b>FIFTY 118S SUB</b>	Active subwoofer, 18" woofer, 1500 W RMS amp	<b>20.328,00</b>	<b>25.410,00</b>
<b>IS Installation SERIES</b>			
<b>IS 4TB</b>	Passive wooden speaker, 4" Fullrange 8ohms, 40W RMS Power, PHOENIX connection, Bracket included, black finish	<b>1.048,00</b>	<b>1.310,00</b>
<b>IS 4TW WHITE</b>	Passive wooden speaker, 4" Fullrange 8ohms, 40W RMS Power, PHOENIX connection, Bracket included, White finish	<b>1.204,00</b>	<b>1.505,00</b>
<b>IS 5TB</b>	Passive wooden speaker, 5" Fullrange 8ohms, 60W RMS Power, PHOENIX connection, Bracket included, black finish	<b>1.204,00</b>	<b>1.505,00</b>
<b>IS 5TW WHITE</b>	Passive wooden speaker, 5" Fullrange 8ohms, 60W RMS Power, PHOENIX connection, Bracket included, white finish	<b>1.344,00</b>	<b>1.680,00</b>
<b>IS 6TB</b>	Passive wooden speaker, 6.5" coaxial+driver Fullrange 8ohms, 100W RMS Power, PHOENIX connection, Bracket included, black finish	<b>2.252,00</b>	<b>2.815,00</b>
<b>IS 6TW WHITE</b>	Passive wooden speaker, 6.5" coaxial+driver Fullrange 8ohms, 100W RMS Power, PHOENIX connection, Bracket included, white finish	<b>2.544,00</b>	<b>3.180,00</b>
<b>IS 25TB</b>	Passive wooden speaker, 2x5"+driver, 8ohms, 120W RMS Power, PHOENIX connection, black finish, same accessories as VIO X 205	<b>3.144,00</b>	<b>3.930,00</b>
<b>IS 25TW WHITE</b>	Passive wooden speaker, 2x5"+driver, 8ohms, 120W RMS Power, PHOENIX connection, white finish, same accessories as VIO X 205	<b>3.440,00</b>	<b>4.300,00</b>
<b>IS 26TB</b>	Passive wooden speaker, 2x6.5"+driver, 8ohms, 250W RMS Power, 2 coverage options available (60x90° rotatable horn or 100x15° waveguide) PHOENIX connection, black finish, same accessories as VIO X 206	<b>4.780,00</b>	<b>5.975,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>IS 26TW WHITE</b>	Passive wooden speaker, 2x6.5"+driver, 8ohms, 250W RMS Power, 2 coverage options available (60x90° rotatable horn or 100x15° waveguide) PHOENIX connection, white finish, same accessories as VIO X 206	<b>5.240,00</b>	<b>6.550,00</b>
<b>IS 8S</b>	Passive subwoofer 8" , 8ohms, 250W RMS Power, black finish	<b>2.696,00</b>	<b>3.370,00</b>
<b>IS 8SW WHITE</b>	Passive subwoofer 8" , 8ohms, 250W RMS Power, white finish	<b>2.992,00</b>	<b>3.740,00</b>
<b>IS 12S</b>	Passive subwoofer 12" , 8ohms, 250W RMS Power, black finish	<b>3.440,00</b>	<b>4.300,00</b>
<b>IS 12SW WHITE</b>	Passive subwoofer 12" , 8ohms, 250W RMS Power, white finish	<b>3.592,00</b>	<b>4.490,00</b>
<b>IA Amplifier SERIES</b>			
<b>IA504R</b>	4 Channels HALF-RACK POWER AMP, 4x125 W RMS and 4 Ohms, DSP on board, VU-Meter on front panel, Mono / Bridge configuration, RD Net interface	<b>9.124,00</b>	<b>11.405,00</b>
<b>IA504D</b>	4 Channels HALF-RACK POWER AMP, 4x125 W RMS and 4 Ohms, DSP on board, VU-Meter on front panel, Mono / Bridge configuration, Dante interface	<b>11.360,00</b>	<b>14.200,00</b>
<b>INGENIA SERIES</b>			
<b>IG1T</b>	2-way Active Speaker 2x6.5" neo woofers, 1" comp. driver, 400W digipro® G3, max SPL 128 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 195x536x271mm (7.68x21.10x10.67in), Weight 10,8Kg – 23.81lbs.	<b>7.924,00</b>	<b>9.905,00</b>
<b>IG2T</b>	2-way Active Speaker 2x8" neo woofers, 1" comp. driver, 400W digipro® G3, max SPL 128 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 228x646x315mm (8.98x25.43x12.40in), Weight 12,8Kg – 28.22lbs.	<b>8.676,00</b>	<b>10.845,00</b>
<b>IG3T</b>	2-way Active Speaker 2x10" neo woofers, 1.4" comp. driver, 900W/RMS digipro® G3, max SPL 132 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 280x806x393mm (11.02x31.73x15.47in), Weight 20,8Kg – 45.86lbs.	<b>12.112,00</b>	<b>15.140,00</b>
<b>IG4T</b>	2-way Active Speaker 4x6.5" neo woofers, 1.4" comp. driver, 900W/RMS digipro® G3, max SPL 132 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 195x956x271mm (7.68x37.64x10.67in), Weight 18,2Kg – 40.12lbs.	<b>12.852,00</b>	<b>16.065,00</b>
<b>IG4T WHITE</b>	2-way Active Speaker 4x6.5" neo woofers, 1.4" comp. driver, 900W/RMS digipro® G3, max SPL 132 dB, 56 bit DSP, OLED display with control knob, digital steering coverage, infrared EPD (Element Position Detection) system. Dimensions: 195x956x271mm (7.68x37.64x10.67in), Weight 18,2Kg – 40.12lbs.	<b>12.852,00</b>	<b>16.065,00</b>
<b>ES SERIES</b>			
<b>ES 503</b>	3-amped 1000 W stereo sound system. 2x tops with 4x 3" full-range speakers with logarithmic position, double-ringed phase plug and vertical digital steering. 1x 12" active subwoofer. 3 inputs, Bluetooth, Mix out, OLED display with advanced user interface.	<b>6.580,00</b>	<b>8.225,00</b>
<b>ES 503 WHITE</b>	3-amped 1000 W stereo sound system. 2x tops with 4x 3" full-range speakers with logarithmic position, double-ringed phase plug and vertical digital steering. 1x 12" active subwoofer. 3 inputs, Bluetooth, Mix out, OLED display with advanced user interface. WHITE	<b>6.580,00</b>	<b>8.225,00</b>
<b>ES 802</b>	Bi-amped 1200 W system. 2x tops with 4x 3" full-range speakers with logarithmic position, double-ringed phase plug and vertical digital steering. 1x 12" active subwoofer.	<b>5.532,00</b>	<b>6.915,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>ES 1002</b>	1800 W Active PA System. Sub and Top Cover included	<b>10.952,00</b>	<b>13.690,00</b>
<b>ES 1203</b>	2400W stereo system	<b>14.948,00</b>	<b>18.685,00</b>
<b>ES 1203 WHITE</b>	2400W stereo system. WHITE	<b>14.948,00</b>	<b>18.685,00</b>
<b>ES 1203 TOP</b>	Satellite speaker for ES 1203 system	<b>2.392,00</b>	<b>2.990,00</b>
<b>LVX SERIES</b>			
<b>LVX 8</b>	2-way Active Speaker with 400W Digipro® digital bi-amp power, 24-Bit/48Khz DSP, 1 x 8" woofer with 1.5", VC 1" driver with rotatable asymmetric 90°/40°x60° horn, SPL peak 121 dB. Dimensions 260x420x260mm, Weight 9,5 Kg / 20,94 lbs.	<b>3.744,00</b>	<b>4.680,00</b>
<b>LVX 8W</b>	White version (no handles)	<b>3.744,00</b>	<b>4.680,00</b>
<b>LVX 10</b>	2-way Active Speaker with integrated 400W/RMS Digipro® digital bi-amp power, 24-Bit/48Khz DSP, 1 x 10" woofer with 1.5"VC, 1" neodymium driver with rotatable asymmetric 90°/40°x60° horn, max SPL 125 dB. Dimensions 300x483x300mm, weight 12 Kg / 26,45 lbs.	<b>4.040,00</b>	<b>5.050,00</b>
<b>LVX 10W</b>	White version (no handles)	<b>4.040,00</b>	<b>5.050,00</b>
<b>LVX 12</b>	2-way Active Speaker with integrated 800W/RMS Digipro® digital bi-amp power, 24-Bit/48Khz DSP, 1 x 12" woofer with 2 "VC, 1" compression driver with rotatable 90°x40° horn, max SPL 127 dB. Dimensions 360x610x360mm, weight 16,5 Kg / 36,37 lbs.	<b>5.688,00</b>	<b>7.110,00</b>
<b>LVX 12W</b>	White version (no handles)	<b>5.688,00</b>	<b>7.110,00</b>
<b>LVX 15</b>	2-way Active Speaker with integrated 800W/RMS Digipro® digital bi-amp power, 24-Bit/48Khz DSP, 1 x 15" woofer with 2 "VC, 1" compression driver with rotatable 90°x40° horn, max SPL 128 dB. Dimensions 430x680x430mm, weight 20 Kg / 44,09 lbs.	<b>5.980,00</b>	<b>7.475,00</b>
<b>LVX 15W</b>	White version (no handles)	<b>5.980,00</b>	<b>7.475,00</b>
<b>LVX XM12</b>	2-way coaxial active monitor, with one 1" CD exit (1.4" voice coil) and one 12" woofer (2.5" voice coil), 600 W DIGIPRO® G3 class D amplifier, max 127 dB SPL, DSP 56 bit, AD/DA Converter: 24 bit / 48 kHz, horn coverage (HxV) 90 x 70°, 8 preset configurations, mic/line switch, Cabinet: Plywood with black pvc cover. Dimensions: 515x460x 370 mm, Weight: 20,1 kg (44,31 lb)	<b>7.028,00</b>	<b>8.785,00</b>
<b>LVX P5</b>	LVX P5 is a passive speaker equipped with a full-range single transducer (5" LF and 1" HF). The most efficient acoustic design, allowing an extended coverage pattern (135°x135°) and a vigorous SPL up to 115 dB, makes this mini full range system the perfect solution to render speech or background music in small venues.	<b>1.204,00</b>	<b>1.505,00</b>
<b>LVX P5 WHITE</b>	LVX P5 is a passive speaker equipped with a full-range single transducer (5" LF and 1" HF). The most efficient acoustic design, allowing an extended coverage pattern (135°x135°) and a vigorous SPL up to 115 dB, makes this mini full range system the perfect solution to render speech or background music in small venues.	<b>1.204,00</b>	<b>1.505,00</b>
<b>LVX P8</b>	Full range LVX P8 provides a 90°x70° dispersion pattern and is equipped with a rotatable horn to guarantee the same HF coverage even in case of horizontal install.	<b>1.652,00</b>	<b>2.065,00</b>
<b>LVX P8 WHITE</b>	White version	<b>1.652,00</b>	<b>2.065,00</b>
<b>LVX P10</b>	Full range LVX P10 provides a 90°x70° dispersion pattern and is equipped with a rotatable horn to guarantee the same HF coverage even in case of horizontal install.	<b>1.788,00</b>	<b>2.235,00</b>
<b>LVX P10 WHITE</b>	White version	<b>1.788,00</b>	<b>2.235,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>LVX P12</b>	Full range LVX P12 provides a 90°x60° dispersion pattern and is equipped with a rotatable horn to guarantee the same HF coverage even in case of horizontal install	<b>2.392,00</b>	<b>2.990,00</b>
<b>LVX P12 WHITE</b>	White version	<b>2.392,00</b>	<b>2.990,00</b>
<b>LVX P15</b>	Full range LVX P15 provides a 90°x60° dispersion pattern and is equipped with a rotatable horn to guarantee the same HF coverage even in case of horizontal install.	<b>2.836,00</b>	<b>3.545,00</b>
<b>LVX P15 WHITE</b>	White version	<b>2.836,00</b>	<b>3.545,00</b>
<b>LVX PSW15</b>	Passive subwoofer LVX PSW15 has been designed to render low end frequencies in small to medium-sized LVX P PA or fixed installations. The system is able to provide 1000 W power at 8 Ohms for a maximum of 130 dB SPL.	<b>3.744,00</b>	<b>4.680,00</b>
<b>LVX PSW15 WHITE</b>	White version	<b>3.744,00</b>	<b>4.680,00</b>
<b>SIGMA SERIES</b>			
<b>Sigma S115</b>	2-way Active Speaker 15" woofer 1000W digipro® G2, 56 bit high resolution DSP, 46Hz - 20.000Hz, max SPL 133 dB, Dimensions: 590x765x533mm, Weight 33 Kg / 72,6 lbs.	<b>9.264,00</b>	<b>11.580,00</b>
<b>Sigma S215</b>	3-way Active Speaker 2x15" woofer +1.4" compression driver, 1400W digipro® G2, 56 bit high resolution DSP, 42Hz - 20.000Hz, max SPL 139 dB, Dimensions: 590x1215x533mm, Weight 50 Kg / 110 lbs.	<b>11.664,00</b>	<b>14.580,00</b>
<b>Sigma S118</b>	Active Subwoofer 18"/4" VC Bassreflex ,1400W, max SPL 134 dB, 56 bit high resolution DSP, 32Hz - 110Hz, Dimentions: 509x815x533, Weight 38 Kg / 83,6 lbs.	<b>9.264,00</b>	<b>11.580,00</b>
<b>Sigma S115F</b>	2-way Active Speaker 15" woofer 1000W digipro® G2, 56 bit high resolution DSP, 46Hz - 20.000Hz, max SPL 133 dB, Dimensions: 590x765x533mm, Weight 33 Kg / 72,6 lbs. Flyable	<b>10.172,00</b>	<b>12.715,00</b>
<b>Sigma S218</b>	Bass-reflex Subwoofer 2x18".180W RMS.	<b>15.704,00</b>	<b>19.630,00</b>
<b>FLEXSYS SERIES</b>			
<b>F 212</b>	Selfpowered 2-way loudspeaker, integrated 750W/RMS digipro™ digital power, 2 x 12" high power woofers incl. ADC™ phase alignment, 1 x 1" RCF neodymium compression driver , rotatable 60°x40° horn, SPL max. 132 dB, 50Hz-20KHz, dimensions 360x930x500mm, weight 31,5 kg/69,44lbs	<b>10.756,00</b>	<b>13.445,00</b>
<b>F 315</b>	Selfpowered 3-way loudspeaker, integrated 750W/RMS digipro™, 1 x 15" high power woofer, 1x 6" hornloaded mid range driver, 1 x 1" compression driver, rotatable 90°x40° CD-Horn, 12 x M10 rigging points, SPL max. 131 dB, 47Hz-20KHz, dimensions 440x880x500mm, weight 31 kg/68,2lbs	<b>11.664,00</b>	<b>14.580,00</b>
<b>FMX 10</b>	FMX is an active 2-way coaxial stage monitor series encompassing 3 models (10,12 and 15") equipped with 400 RMS (for FMX 10) or 600 RMS (for FMX 12 and 15) Class D amplifiers.	<b>3.284,00</b>	<b>4.105,00</b>
<b>FMX 12</b>	FMX is an active 2-way coaxial stage monitor series encompassing 3 models (10,12 and 15") equipped with 400 RMS (for FMX 10) or 600 RMS (for FMX 12 and 15) Class D amplifiers.	<b>4.040,00</b>	<b>5.050,00</b>
<b>FMX 15</b>	FMX is an active 2-way coaxial stage monitor series encompassing 3 models (10,12 and 15") equipped with 400 RMS (for FMX 10) or 600 RMS (for FMX 12 and 15) Class D amplifiers.	<b>4.780,00</b>	<b>5.975,00</b>
<b>KL Series</b>			
<b>KL 10</b>	KL 10 is a 2-way active speaker equipped with one 10" woofer and one 1" compression driver (1" voice coil).	<b>2.252,00</b>	<b>2.815,00</b>
<b>KL 12</b>	KL 12 is a 2-way active speaker equipped a 12" woofer and one 1" compression driver (1.35 voice coil)	<b>2.544,00</b>	<b>3.180,00</b>
<b>KL 15</b>	KL 15 is a 2-way active speaker equipped a 15" woofer and 1" compression driver (1.35 voice coil).	<b>2.992,00</b>	<b>3.740,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>OPERA SERIES</b>			
<b>OPERA 10</b>	2 way active speaker 10" woofer, 600W RMS, max SPL 128 dB, asymmetrical CD horn, Dimensions: 300x552x301 mm, weight: 12.3 kg (27.12 lbs.)	<b>2.992,00</b>	<b>3.740,00</b>
<b>OPERA 12</b>	2 way active speaker 12" woofer, 600W RMS, max SPL 129 dB, asymmetrical CD horn, Dimensions: 350x642x349 mm, weight: 14.3 kg (31.53 lbs.)	<b>3.440,00</b>	<b>4.300,00</b>
<b>OPERA 15</b>	2 way active speaker 15" woofer, 600W RMS, max SPL 130 dB, asymmetrical CD horn, Dimensions: 420x722x419 mm, weight: 18.3 kg (40.34 lbs.)	<b>3.744,00</b>	<b>4.680,00</b>
<b>B-HYPE SERIES</b>			
<b>B-Hype 8</b>	The new B-HYPE 8 is a versatile active speaker. It is equipped with one 1" compression driver (1" voice coil), and one 8" woofer (1.5" voice coil). The dispersion pattern is asymmetrical on vertical axis, and it is diversified (top and bottom) on the horizontal one. This allows a narrower and more efficient sound coverage, and a better performance in case of reverberant environments.	<b>1.204,00</b>	<b>1.505,00</b>
<b>B-Hype 10</b>	The new B-HYPE 10 is a versatile active speaker. It is equipped with one 1" compression driver (1" voice coil), and one 10" woofer (1.5" voice coil). The dispersion pattern is asymmetrical on vertical axis, and it is diversified (top and bottom) on the horizontal one. This allows a narrower and more efficient sound coverage, and a better performance in case of reverberant environments.	<b>1.496,00</b>	<b>1.870,00</b>
<b>B-Hype 12</b>	The new B-HYPE 12 is a versatile active speaker. It is equipped with one 1" neodymium compression driver (1" voice coil), and one 12" woofer (2" voice coil). The dispersion pattern is asymmetrical on vertical axis, and it is diversified (top and bottom) on the horizontal one. This allows a narrower and more efficient sound coverage, and a better performance in case of reverberant environments.	<b>1.944,00</b>	<b>2.430,00</b>
<b>B-Hype 15</b>	The new B-Hype 15 is a versatile active speaker. It is equipped with one 1" neodymium compression driver (1" voice coil), and one 15" woofer (2" voice coil). The dispersion pattern is asymmetrical on vertical axis, and it is diversified (top and bottom) on the horizontal one. This allows a narrower and more efficient sound coverage, and a better performance in case of reverberant environments.	<b>2.392,00</b>	<b>2.990,00</b>
<b>B-HYPE MOBILE HT</b>	B-Hype M mixes the professional acoustic performance of the B-H family with the most advanced versatility of a complete portable PA equipped with a wireless microphone system, audio media player with Bluetooth connection, SD card and USB port, a long lasting battery, wheels and a retractable top handle	<b>3.744,00</b>	<b>4.680,00</b>
<b>B-HYPE MOBILE BT</b>	B-Hype M mixes the professional acoustic performance of the B-H family with the most advanced versatility of a complete portable PA equipped with a wireless microphone system, audio media player with Bluetooth connection, SD card and USB port, a long lasting battery, wheels and a retractable top handle	<b>3.744,00</b>	<b>4.680,00</b>
<b>SUB SERIES</b>			
<b>SUB 612</b>	Just like 15" and 18" models of the family, bass-reflex SUB 612 features a 600W RMS Class-D Power Amplifier with SMPS, delivers outstanding sound pressure levels in spite of a very compact housing (only 19.8 Kg -43,65 lbs) and provides an impressively precise low-end reproduction.	<b>3.144,00</b>	<b>3.930,00</b>
<b>SUB 615</b>	SUB615 is a bass-reflex active subwoofer featuring a 600W RMS Class D SMPS Power Amplifier and is equipped with a 15" transducer.	<b>4.332,00</b>	<b>5.415,00</b>
<b>SUB 618</b>	SUB618 is a bass-reflex active subwoofer featuring a 600W RMS Class D Power Amplifier with SMPS and is equipped with a 18" transducer.	<b>5.532,00</b>	<b>6.915,00</b>
<b>SUB 915</b>	SUB 915 is equipped with a single premium 15" woofer housed in a bass-reflex design.	<b>8.368,00</b>	<b>10.460,00</b>
<b>SUB 918</b>	SUB 918 is equipped with a single 18" premium woofer housed into a bass-reflex design.	<b>10.620,00</b>	<b>13.275,00</b>

# dBTechnologies

Varenr.	Tekst	excl.moms	incl. moms
<b>MINIBOX SERIES</b>			
<b>K 70</b>	Compact Active Speaker 1x 5" dB Bass + Tweeter, 100 W / Music, 50 W / RMS, 101 dB SPL max, 100 – 16.000Hz, Dimensions 170x270x185 mm, Weight 3,5 Kg	<b>1.344,00</b>	<b>1.680,00</b>
<b>K 162</b>	Compact Active Speaker 2x 6,5" dB Bass + Tweeter, 130 W / Music, 65 W / RMS, 110 dB SPL max, 85 – 19.000 Hz, Dimensions 210x350x270mm, Weight 5,5 Kg	<b>1.652,00</b>	<b>2.065,00</b>
<b>K 300</b>	Compact Active Speaker 2x 6,5" neodymium woofer with 1,5" VC, 1" neodymium driver, Class-D Bi-Amp 120 W/RMS, max. SPL peak 118 dB, Dimensions 210x350x270 mm, weight 5 Kg/11,02 lbs.	<b>2.544,00</b>	<b>3.180,00</b>
<b>L 160 D</b>	Active Speaker 2x5" 160 Watt	<b>2.252,00</b>	<b>2.815,00</b>
<b>CONTROLLERS</b>			
<b>AC26N</b>	Digital Audio Processor, 2 in - 6 out, Full Range power supply, RDNet Hardware Interface, USB interface, remotable via RDNet or USB. Max input level 21dBu (without pad) / 27dBu (with -6dB pad). Max output level 21dBu. DSP Processing: 28/56bit - 48Khz. A/D and D/A Converts: 24bit - 96Khz.	<b>6.428,00</b>	<b>8.035,00</b>
<b>ASX 24</b>	2-Way/3-Way stereo - 4-Way Mono Active Crossover. 2x XLR-Input with 25Hz high-pass filter switch, 6x XLR-Output, high quality 24dB/octave slope Linkwitz-Riley filters, In/Out level controls, xover frequency selection for all bands, mute key and phase reversal for each band, adjustable delay time up to 2ms for outputs, "LOW SUM" function to convey the whole LF range of L&R channels to a mono sub out, multiband limiter with adjustable threshold.	<b>1.652,00</b>	<b>2.065,00</b>
<b>DSX 2040</b>	Digital 2 in 4 controller, 48Khz/32-bit signal processing, dynamic range >110dB(A), 3000ms total delay, 4 parameter. EQs per in- and output, programmable x-over and routing-section, editable limiter per output, large LC-Display, bank for 30 presets, USB-interface for programming and data-transfer, 19", 1U, in- and outputs on balanced XLR.	<b>8.076,00</b>	<b>10.095,00</b>
<b>Switch 6</b>	2 x XLR-Input into 2x6 XLR-Output, 1 Unit with LED Display and Remote Control. Up to 6 units in parallel mode.	<b>3.884,00</b>	<b>4.855,00</b>